

5500SERIES



HEAVIER OPERATING WEIGHT

With 5,567 to 6,039 lbs. of weight on the ground (varies by model), you'll have one of the sturdiest tractors in its class.



POWER STEERING

Equipped with power steering, the 5500 series also boasts a tight turning radius designed to make your work easier, faster, and more efficient.



SPACIOUS DECK

A spacious, semi-flat deck with rubber mat and side shift levers helps ease operator fatigue on long days in the field.

5500 SERIES ATTACHMENTS

| TRACTOR | 5545 4WD | 5555 4WD |
|---|----------------|----------------|
| LOADER MODEL | 5545-4L | 5555-4L |
| Standard Bucket Size [in] | 72 | 78 |
| Maximum Lift Height [in] | 120 | 128 |
| Dig Depth [in] | 5 | 6 |
| Lift Capacity to Full Height at Pivot Pin [lbs] | 2950 | 3000 |
| Breakout Force [lbs] | 4950 | 4825 |
| Shipping Weight [lbs] | 1600 | 1960 |
| BACKHOE MODEL | 75B | |
| Standard Bucket Size [in] | 18 | |
| Maximum Dig Depth [in] | 116 | |
| Dig Depth 2' Flat Bottom [in] | 115 | |
| Dig Force Bucket [lbs] | 5676 | |
| Dig Force Dipper [lbs] | 2754 | |
| Shipping Weight [lbs] | 2036 | |



5500 SERIES SPECIFICATIONS

| TRACTOR | 5545 4WD | 5555 4WD |
|-------------------------------------|---|---|
| ENGINE | | |
| Type | Four-stroke, Naturally Aspirated, Direct Injection, Water Cooled Diesel Engine | Four-stroke, Turbocharged, Direct Injection, Water Cooled Diesel Engine |
| Engine HP (kW) @ RPM | 43 (32) @ 2300 | 55 (41) @ 2100 |
| Displacement [in ³ (cc)] | 161.7 (2650) | |
| Number of Cylinders | 3 | |
| Bore & Stroke [in] | Bore: 3.78, Stroke: 4.8 | |
| Fuel Tank [gal (L)] | 12 (45) | 17.1 (64.7) |
| DRIVE TRAIN | | |
| Transmission | Forward / Reverse Shuttle Synchromesh with Speeds Section Synchromesh & Constant Mesh Range | |
| Number of Speeds | 8F/ 8R | |
| Clutch | Dual Dry with Cerametallic Lining | |
| Brakes | Fully Enclosed Dry Disc (7" Diameter) | |
| PTO | | |
| Type | Independent | |
| Rear PTO RPM | 540 @ 2058 | 540 @ 2059 |
| PTO HP (kW) | 34 (25.3) | 45 (33.6) |
| HYDRAULICS | | |
| Type | Open Center with Position & Draft Controls | |
| Implement Pump Output [gpm (L/min)] | 10.9 (41.2) | 11.2 (42.4) |
| Maximum Total Flow [gpm (L/min)] | 15.9 (60.1) | 15.8 (59.7) |
| 3-Point Hitch | CAT I & II w/ Telescopic Stabilizers & Flex Links | |
| Lift Capacity [lb (kg)] | 3969 (1800) | |
| ELECTRICAL | | |
| Battery | 12 V, 925 CCA | |
| Alternator | 12 V, 55 A | |
| DIMENSIONS | | |
| Overall Length [in (mm)] | 134 (3403) | 140 (3556) |
| Overall Width [in (mm)] | 72.5 (1841) | 79 (2006) |
| Overall Height [in (mm)] | 93.3 (2369) | 98.8 (2509) |
| Wheelbase [in (mm)] | 85.1 (2161) | 85.2 (2164) |
| Minimum Ground Clearance [in (mm)] | 15.16 (385) | 16.35 (435) |
| Turning Radius [ft (m)] | 10.8 (3.29) | |
| Weight [lb (kg)] | 5567 (2525) | 6039 (2745) |
| WHEELS & TIRES | | |
| AG [Front/Rear] | 9.5 x 20 / 13.6 x 28 | 9.5 x 24 / 14.9 x 28 |
| IND [Front/Rear] | 10.5 / 80 x 18 / 16.9 x 24 | 12.5 / 80 x 18 / 16.9 x 24 |